

Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Trade name webercol flex2 multi

Safety data sheet no.: XXP015639

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Ready-to-use mortar

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Saint- Gobain Weber Cemarksa S.A.

C/ C-17, Km. 2

08110 Montcada i Reixac (Barcelona)

tf: +34 935726500

1.4 Emergency telephone number: Emergency Telephone:

112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Results of in vitro- tests have shown that cement based mixtures with more than 1% of cement cause serious skin irritation and serious eye damage, therefore the classification of these mixtures regarding H315 and H318 is not based on the calculation of the ingredients or the pH in this case.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS05 GHS07

Signal word Danger

Hazard-determining components of labelling:

Cement, portland, chemicals

Hazard statements

H315 Causes skin irritation.

(Contd. on page 2)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

(Contd. of page 1)

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P280 Wear protective gloves / eye protection / face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

2.3 Other hazards

Under the conditions of conservation, the reducing agent used keeps the content of soluble chromium (VI) below 2 ppm until the expiration date indicated.

Results of PBT and vPvB assessment PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

SECTION 3: Composition/information on ingredients

3.2 Chemical characterisation: Mixtures

Description: Mixture of substances listed below with non hazardous additions.

Dangerous compor	nents:	
	limestone substance with a Community workplace exposure limit	>50%
	Cement, portland, chemicals Eye Dam. 1, H318; Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 1 % Eye Dam. 1; H318: C ≥ 1 %	25-50%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg3H2(SiO3)4) substance with a Community workplace exposure limit	1-2%

SVHC Void

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information Immediately remove any clothing soiled by the product.

After inhalation Supply fresh air; consult doctor in case of complaints.

After skin contact

If skin irritation continues, consult a doctor.

Immediately rinse with water.

(Contd. on page 3)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

After eye contact

(Contd. of page 2)

Rinse opened eye for several minutes under running water. Then consult doctor. Rinse liquid should be tempered (20-30°C).

After swallowing If symptoms persist consult a doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

Use methods suitable to surrounding conditions.

Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of dust.

Ensure adequate ventilation.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Pick up mechanically.
- 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Provide suction extractors if dust is formed.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Do not store together with acids.

Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 4)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

Protect from humidity and water.

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS No. Desig	gnation of material % Type Value Unit
CAS: 1317-65-3	limestone
TWA (Italy)	Long-term value: 10 mg/m³ (e)
CAS: 65997-15-1	Cement, portland, chemicals
AGW (Germany)	Long-term value: 5 E mg/m³ DFG
LEP (Spain)	Long-term value: 4 mg/m³ fracción respirable: e, d
TWA (Italy)	Long-term value: 1 mg/m³ (e, j), A4
VLE (Portugal)	Long-term value: 1 mg/m³ Fração resp.;A4,função pulm.,sintomas resp.,asma
HTP (Finland)	Long-term value: 5* 1** mg/m³ *hengittyvä/inhalerbart, **alveolijae/respirabel
CAS: 14807-96-6	Talc (Mg3H2(SiO3)4)
MAK (Germany)	asbestfaserfrei, alveolengängige Fraktion
GV (Denmark)	0.3 fiber/cm3, K
LEP (Spain)	Long-term value: 2* mg/m³ *sin fibras de amianto, fracción respirable d, e
TWA (Italy)	Long-term value: 2** mg/m³, 0.1 fibre/cc* ppm *contenente: A1,(m) **senza fibre: A4, (e),(j)
VLE (Portugal)	Long-term value: 2* 0.1f/c** mg/m³ *sem:A4:**com fibras:A1;fibrose,função pulm.
OEL (Sweden)	Long-term value: 2* 1** mg/m³ *totaldamm **respirabel fraktion
HTP (Finland)	Long-term value: 0.5* 2** 1*** mg/m³ *kuitumainen,kuitua/cm3,**hengittyvä pöly,***alv.

Additional Occupational Exposure Limit Values for possible hazards during processing:

Total inhalable dust: 10 mg/m³ Respirable dust (< 5 μm): 4 mg/m³

Quartz respirable dust (< 5 µm): 0,15 mg/m³

Additional information:

The applicable TRGS 900 (MAK list) was used as the basis for the preparation and/or revision of this safety data sheet.

(Contd. on page 5)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

(Contd. of page 4)

8.2 Exposure controls

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Use a moisturising skin cream after processing the product.

Respiratory protection:

Short term filter device:

Filter P2.

In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Protective gloves.

Material of gloves Nitrile impregnated cotton gloves complying with the standard EN 374-1.

Eye protection: Tightly sealed goggles **Body protection:** Protective work clothing.

9.1 Information on basic physical and cher General Information	mical properties
Appearance:	
Form:	Powder
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Alkaline
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Flash point:	Not applicable
Flammability (solid, gas):	Product is not flammable.
Ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Oxidising properties	Not determined.
Vapour pressure:	Not applicable.
	(Contd. on page 6)

(Contd. on page 6)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

(Contd. of page 5)

Density:

Relative density
Vapour density
Not applicable.
Evaporation rate
Not applicable.

Solubility in / Miscibility with

Water: Hardens when in contact with water.

Segregation coefficient (n-octanol/water) log

Pow: Not determined.

Viscosity:

dynamic:kinematic:
Not applicable.
Not applicable.

Solvent content:

EU-VOC (%) 0.00 % EU-VOC (g/L) 0.0 g/l Solids content: 100.0 %

9.2 Other informationNo further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity Not reactive under normal conditions of use
- 10.2 Chemical stability Stable at recommended storage conditions

Thermal decomposition / Conditions to be avoided:

No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions Reacts with acids
- **10.4 Conditions to avoid** No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Compo	nents	Type	Value	Species
CAS: 1	317-65	-3 limestone		
Oral	LD50	>5,000 mg/kg (Rat)		
CAS: 6	5997-1	5-1 Cement, portland, cl	nemicals	
Dermal	LD50	>2,000 mg/kg (Rabbit)		

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

(Contd. on page 7)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

(Contd. of page 6)

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity: Not classified as harmful to aquatic life

Type of te	st Effective concentration Method Assessment
CAS: 1317	7-65-3 limestone
LC50/96h	>10,000 mg/l (Oncorhynchus mykiss (Rainbow trout))
EC50/48h	>1,000 mg/l (Daphnia magna)
EC50/72h	>200 mg/l (Algae)

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

Behaviour in environmental systems:

12.4 Mobility in soil No further relevant information available.

Ecotoxical effects:

Remark:

The product contains substances which cause a local pH change and thus have a detrimental effect on fish and bacteria.

Additional ecological information:

General notes: Do not allow product to reach ground water, water course or sewage system.

12.5 Results of PBT and vPvB assessment

PBT: Does not contain PBT substances. **vPvB:** Does not contain vPvB substances.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Dispose of the product in accordance with national and local regulations.

European waste catalogue

Possible waste code. The concrete waste code depends on the source of the waste.

-		
1		wastes from cement-based composite materials other than those mentioned in 10 13 09 and 10 13 10
1	10 13 14	waste concrete and concrete sludge
H	HP4	Irritant - skin irritation and eye damage
H	HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
H	HP13	Sensitising

(Contd. on page 8)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

(Contd. of page 7)

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleaning agent: Thoroughly shake out sacks.

SECTION 14: Transport information	on	
14.1 UN-Number ADR, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name ADR, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annomarpol and the IBC Code	ex II of Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1272/2008 (CLP)

Regulation (EC) No 1907/2006 (REACH) (Candidate List, Annexes XIV and XVII)

Contains Portland cement with a soluble chromium VI content under 2 ppm during the conservation period indicated on the packaging

Labelling according to Regulation (EC) No 1272/2008 cf. section 2

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

REGULATION (EC) No 1907/2006 ANNEX XVII

The marketing and use of cement is subject to a restriction on the content of soluble Cr (VI) (REACH Annex XVII point 47 Chromium VI compounds)

Conditions of restriction: 47

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 9)



Printing date 24.02.2020 Version number 2 Revision: 24.02.2020

Trade name webercol flex2 multi

(Contd. of page 8)

Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

Department issuing SDS: Environment, Health and Safety Department (EHS)

Contact: David Gonzalo; Tf.: +34 686517274

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern (REACH regulation)

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Skin Sens. 1B: Skin sensitisation - Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3